

AIA/CES Reporting Details

All attendees will be eligible to receive:

- 1 LU (AIA continuing education) or
- 1 TU of IDP supplementary education credit.

All attendees at your site will submit for credit by completing the webinar survey/report form. The URL to the survey/form will be listed at the end of the presentation. Certificates of Completion can be download at the end of the survey.

Continuing education questions can be directed to knowledgecommunities@aia.org.



twitter> #AIATAP


AIA/CES Compliance Statement

"AIA Knowledge" is a Registered Provider with The American Institute of Architects Continuing Education Systems. Credit earned on completion of this program (Course #T12002) will be reported to CES Records for AIA members. Certificates of Completion will be sent to all attendees.

This program is registered with the AIA/CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product. Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.



twitter> #AIATAP





AIA/CES Learning Objectives


- Learn LEAN thinking, including set based design and target value design strategies. Learn to apply a rigorous technical, analytic and research-based approach to design and decision making to arrive at best value solutions.
- 2. Understand the heightened level of team integration and new models of knowledge sharing, through the accelerated design-build competition and project delivery process.
- 3. Identify best practices for achieving aggressive building performance, cost and project delivery objectives.
- 4. Discover how an integrated building weaves interdependent systems to achieve a net result greater than the sum of individual systems.





twitter> #AIATAP















Welcome



Introduce






Todd, Jack

- •As part of the Recovery Act, solicitation issued in Fall of 2009 for Design —Build teams to submit qualifications for 175,000 s.f. modernization of an existing warehouse on the Federal Center South campus in Seattle, to house the Seattle District USACE.
- •Sellen and ZGF have been working together since the early 1990s on several large Microsoft projects Sellen asked ZGF to design their new headquarters ZGF asked Sellen to build-out our new offices
- Larger team including kpff engineers and Flack + Kurtz mechanical and electrical engineers
- Phase II of the solicitation consisted of an 18 week design competition against two other teams resulting in schematic level design that guaranteed performance and budget.



Todd, Jack

- After award, the integrated project team grew to include mechanical and electrical subcontractors as well as the reclaimed timber subcontractor.
- •Mechanical subcontractor brought on in design-assist role wherein they actually produced the construction drawings, but Flack+Kurtz remained as the engineer of record
- Electrical subcontractor brought on as typical design-build entity.




AUTOMATIC ANIMATION - ONE CLICK ONLY!

- •The site for the project is located along the Duwamish Waterway just south of downtown Seattle. The original waterway meandered considerably, but the Army Corps dredged it and straightened it out in the early 1900s in order to promote commerce.
- •The site was originally part of the Duwamish Tidal Basin, which not only provided inspiration for the design solution, but also posed significant challenges for the buildings's foundations



- •The existing Federal Center South Campus contains two primary buildings
- •The 1201 building, originally built by Ford Motor Company as a assembly plant in the 1930's, was, in its day, its own form of Recovery Act, and has been converted to office space where the Corps is currently located.
- •The 1202 building was built in the 1940's, and was used by Boeing to build missiles for WWII, and we discovered, was later used as a morgue.
- •The 1202 building is the warehouse originally slated for "modernization".
- •Our site is the northwest corner of the campus, made possible by demolishing the north half of the 1202 building.




AUTOMATIC ANIMATION - ONE CLICK ONLY

•With the Army Corps as the tenant, the building had to comply with the Department of Defense anti-terrorism requirements including setback distances from vehicular traffic




•The siting of the building, along with the required setbacks, offered the opportunity to create two faces to the building that respond to both its formal and natural context.



Todd, Jack



•The design solution embodies a significant culture shift that is being implemented by the leadership of the Seattle district of the Corps.



Todd, Chris

- •One of the primary goals of the Recovery Act is to create High Performance Green Buildings that establish new performance standards for the marketplace.
- •ASHRAE 2007 Baseline = 2030 60%, 30% better than that ~70%
- •Competition Brief: 2/3 Efficiency, 1/3 PV's (\$\$\$)
- •Better, more integrated way?
 - •More money for design, quality.
 - Lower EUI >"Net Zero Ready"

High Performance Green Building

LEED Gold minimum

Employ integrated approach to meet sustainability goals

30% reduction in energy usage compared to ASHRAE 90.1-2007

Install advanced meters for electricity, natural gas, and water

Install solar thermal hot water system (integrated approach determined not cost effective)

Plan for on-site renewable energy systems

Reduce indoor potable water use by at least 20%

Reduce outdoor potable water use by at least 50%

Manage 95th percentile rain event onsite through infiltration

Provide occupancy and daylight sensors

Pre-occupancy flush-out

Salvage, recycle, or reuse at least 50% of construction and demolition waste









Chris, Jack

- Minimum Performance Checklist
- Energy 1 of many H.P. criteria
- •LEED Gold, and many credits above and beyond...
 - •Advanced metering (H₂0, too)
 - Solar hot water



Jack, Tom


GSA FCS example of the EUI target built into the RFP and the contract with M&V.

In order to help clients achieve their goals we need to focus on an integrated design process.

Proposed Betterments

- Geothermal Heat Pump System
- Laminated Glass Skylight at Atrium
- Triple Glazing at Perimeter
- Solar PV Array
- White Capsheet on Roof
- Solar Thermal Hot Water Heating
- Enhanced Lighting Controls
- Rainwater Capture and Reuse
- Smart Building Technology
- Energy Dashboard
- LEED Platinum







Todd, Jack

AUTOMATIC ANIMATION – ONE CLICK ONLY!

- Original Schedule
- Very aggressive, particularly since we had had minimal client input during the design competition
- Design-build has reduced the overall schedule by 1 to 2 years when compared to a conventional GSA design-bid-build procurement.






- Army Corps program
- Major departments governed
- Pulled out meeting spaces from individual departments into the Commons



Chris

AUTOMATIC ANIMATION - ONE CLICK ONLY



Chris

- Designers faster than engineers/modelers
- •Generic Energy Rose (EQUEST)
- •Go Daylight optimized rotated
 - Annual Energy Use
 - •Peak = Equipment cost
- •Tweak evolving atrium scheme
- •UA benefit vs. Bar Building
 - •Envelope = Heat loss, Energy = Money




Todd, Chris

•Three stories triggered progressive collapse requirements




Todd, Chris



Todd, Chris


•The bar of the Oxbow is 60 foot wide with 22 foot structural bays along the length to maximize access to views and daylight, and to right-size the office area for the typical workstation.















- •DEEP PILES extend through the silty and sandy soils to bear on firm Glacial Till... depth of till at 160' deep on average;
- Provides a ROCK-SOLID foundation for the new building, overcoming the risk of soil liquefaction during a seismic event.
- •In addition, the ground level floor is supported not by a slab-on-grade, but by interconnected GRADE BEAMS; so it can also remain unaffected even in the event of soil liquefaction event.




- •In this case, loose, liquefiable soils can be modified to increase the soil's resistance to liquefaction and slope instability.
- •The use of stone columns is a ground improvement technique where stones displace or replace weak soils using either an electrical or hydraulically actuated, cylindrical vibrating probe
- •Stone columns along the western edge of the site stabilize the soil to mitigate the potential for lateral spreading
- •liquefaction-induced settlement could range from nearly 1.5 feet to more than 5 feet in the vicinity of the proposed building



Jack

- Piles on average 160 feet deep.
- •Test piles utilized to determine if geothermal wells would further enhance performance of the building.



Todd, Jack

- •Started with an assessment of the yield that could be harvested from the existing warehouse
- •Modeling used throughout design to not only develop the aesthetic, but to continually crosscheck sizes and quantities to ensure that the use matched the harvest
- Demolition involved careful dis-assembly in order to ensure the maximum yield
- •Existing paint only milkwash, was easily removed via hand-planning and waterjetting to create a rich patina finish
- Erection process has been referred to be akin to "working with tinker toys"



Todd, Jack

- •Over 200,000 board feet of timber and decking has been re-claimed for use in the building.
- •Composite wood beams introduced in order to match number of purlins required with available timber.
- •Additional lumber has been re-purposed to create concrete formwork, as well as other temporary uses during construction.
- Re-use of lumber has resulted in over 99% recycle rate of construction waste




- •Gordon R. Plume Timber Company, who worked with Sellen on the house for a certain software mogul in the Seattle area, provided valuable expertise in grading the timbers and fabricating them for their new use.
- •This view shows the architectural rendering.....



 \bullet This view is from the MEP model illustrating the integration of piping and ductwork with the exposed structure.




- ■Jack, Todd
- ■The same view under construction




Jack

- •Existing timber piles, 16" in diameter, and 40 foot long, extend the full length of the 1202 building at 8'-0" on center
- •Building was sited to minimize the number of timber piles that needed to be removed.
- •In the end, only 55 piles had to be removed, and these piles are being re-used as site benches and for construction means and methods.
- •The remaining piles provide additional soil densification.



Todd, Chris


Session 1: AIA+2030 27 January 2012



Charles


- Explain how we hit these goals
 - Primary Energy
 - •With integrated design
 - Achieving quality in Architectural design
 - •Indoor environment

Session 1: AIA+2030 27 January 2012




Charles

- •Current Prediction
 - •24 EUI 77% vs CBECS, 40% vs ASHRAE
- •Heat & Cool Miniscule
 - Efficient Systems
 - •Heat (Pump) Recovery & Redistribution
- Hot Water small, but less energy by using heat pumps & ASTE Heat Recovery
- Lighting



Chris

- •Seattle Predominantly overcast , fairly clear summer
- •Target D.F ~ 3 in office




Chris, Todd

- Direct/indirect lighting fixtures
- •Structural Module of 22'
- Achieve goals of 25 fc
- •Installed LPD of 0.7



Chris, Jack, Todd


- •Sellen introduced Barcol-Air to the west coast.
- •Energy wave...
- •Chilled beams "sails"
- •Decouple vent + H/C
- •Water 327 x vs Air
- •Low velocity vent in UFAD
- •Barcol Air



Chris


- •Dev of Env in concept w/HVAC
 - •What performance criteria to meet goal?
- •Original goal: Heating No separate perimeter system
 - •Considered triple glazing, separated high temp plenum
 - •But: Higher cost, less comfort (1%) HRS
 - •And *lower energy performance ultimately, per hydronic ???
- •Cooling: Limit C.B density to...Orientation specific shading NW V, E, S

Session 1: AIA+2030 27 January 2012




Charles, Jack, Todd

- · Building orientation, High windows & Skylights maximize daylighting; External Shading controls heat gain
- High Performance Glazing enhances energy efficiency as well as Blast Protection
- Energy use reduced by 30%
 100% Outdoor Filtered Air for Ventilation.
 Healthy Underfloor Air Dist. System
- High efficiency WaterSense fixtures save water
- LEED GOLD Certification
- Building Form and Skin designed to aid in air flow
 Stormwater is actively managed on-site with surface detention & conveyance
- •Thermal Storage provides maximum efficiency for HVAC system Radiant cooling assures thermal comfort while saving energy.
- •During the design competition explored a number of high performance strategies that ultimately had to be set aside in order to meet an initial budget. These were presented as "Betterments" to GSA, that they could incorporate into the project if additional funding became available. GSA embraced this concept and collaborated with design-build team to incorporate geothermal wells, rainwater harvesting, and a glass skylight.
- •Atrium Air handlers (5)
 - •Smoke exhaust enable mixed construction
 - Exposed steel & wood
- •2 other systems for base heat source
 - P.C.
 - GSHP




Chris

- •Loads for annual simulation (F+V, B.E.)
- •Heat load reduced through HX
- •Sim H+C
- •Cooling sign period peaks




Chris

- •??? where can we move energy ???
 - •Heat interior > Perimeter (Hydronu
 - Monitoring warmup vs. day cooling (storage)
 - •Capacity to do a lot of cooling at night in Seattle (typical < 60F ???)




Chris, Jack

- PCM tank capacity for 50% of cooling solving storage problem
- •Melting/freezing point 55F
 - •Base Temp.
 - •Superfast GSHP limited capacity renewable daily




Chris, Jack

- Early comp concept was GSHP integrated design, but more costly than PCM
- Essentially same as PCM
- •Not in Project more cost duplicate, only got small 7% better
- •Additional Betterment \$, Reduce cooling tower (1/2)




Todd, Jack

- •25,000 gallon cistern captures rainwater from all of the roofs
- •Rainwater used for grey water at toilets and cooling tower make-up, as well as for irrigation
- •In addition the rain water, after ozone treatment, is pumped back to the atrium water feature consisting of source stones representing the four tributary rivers that feed into the Duwamish, as well as the Duwamish past and present.



Todd

- •Architectural models architectural team very green in terms of use of Revit. Only one master user at the start of the project. After early frustration, team grew to prefer Revit over AutoCAD. Team particularly excelled at generating presentation graphics. Team underestimated the effort required to extract good quality 2D construction documents from the model.
- •Structural model many versions:
 - •ZGF Revit
 - •Kpff Revit
 - •Sellen wood Revit
 - •MKE, steel detailing Steel detailing program
- •Mechanical utilized CADduct not easy to share files with Revit utilized Navisworks for 3D coordination throughout the design and documentation process but unable to import mechanical systems into architectural and structural models




Todd

- · Lighting, studies for both daylighting and artifical lighting
- •Smoke/CFD: Entire building is an atrium, smoke modeling required to simulate ability to exit the building safely in the event of a significant terrorist event. CFD modeling utilized to assure that condensation will not occur on chilled sails
- •Detailing: wood structure as well as the fact that the structure is exposed throughout created unique detailing situations that required their resolution via 3D modeling




- •Design-build process allowed the introduction of innovative semi-custom systems to be developed for the building, all of which have the ability to be utilized on future projects
- •New vertical shingle design, now part of the manufacturer's standard line
- First use of composite wood beams in the U.S.
- New chilled sail design with perforations, actually performs better than anticipated
- also now becoming part of manufacturer's standard line of products.




Todd, Jack

- •Although integration of systems thoroughly examined via 3D modeling, the actual execution still presented some unknowns.
- Built full-scale mock-up of one bay of the Oxbow.
- Every trade that participated in this R&D lab has changed their means and methods as a result.
- •Design-build process allowed an additional opportunity for the trades to learn how to put the building together in a practice run.



Chris, Jack

• Metering requiring far exceeds that required to meet LEED M&V requirement.





AUTOMATIC ANIMATION - ONE CLICK ONLY



The End



Todd

Introduce

